
SHROUDED IDC **HEADER & STACKER**



(2.00 mm) .0787" PITCH • STMM/ZSTMM SERIES

STMM/ZSTMM

Mates:

TCSD (except -SR)

SPECIFICATIONS

Insulator Material: Black Liquid Crystal Polymer
Terminal Material: Phosphor Bronze Plating: Sn or Au over 50 µ" (1.27 µm) Ni Operating Temp Range: -55 °C to +105 °C with Tin; -55 °C to +125 °C with Gold

PROCESSING

Lead-Free Solderable: SMT Lead Coplanarity: (0.10 mm) .004" max







PLATING OPTION



TAIL OPTION

OPTION

04, 05, 06, 07, 08, 10,

12, 13, 14, 15, 17, 20, 22, 25 (Standard sizes)



= 10 μ" (0.25 μm) Gold on post, Matte Tin on tail

Leave blank for Through-hole

-RA = Right-angle

-SM = Surface Mount

-"XX" = Polarized Position

-LC

= Locking Clip (-SM only) (Manual placement required)


–K = (7.50 mm) .295" DIA Film Pick & Place Pad (-SM only)


-TR

Tape & Reel (–SM only)

-FR

= Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks) (–SM only)













NO. PINS PER ROW

04, 05, 06,

07, 08, 10,

12, 13, 14, 15,

17, 20, 22, 25

(Standard sizes)

STYLE

Specify

LEAD

STYLE

from

chart

PLATING OPTION



Б

-RA

(2.29) .090





-F = Gold flash on post, Matte Tin on tail

-L= 10 µ" (0.25 µm) Gold on post, Matte Tin on tail

> -T= Matte Tin

-"XXX" = Body Height


-"XX" = Polarized Position


ALSO AVAILABLE MOQ Required


Other sizes Other platings

For added mechanical stability, Samtec recommends mechanical board spacers be used in applications with gold or selective gold plated connectors. Contact ipg@samtec.com for more information.

This Series is non-standard, non-returnable.







LEAD STYLE	A (OAL)	MAX BODY HEIGHT
- 75	(9.58) 0.377	(7.42) 0.292
-62	(10.08) 0.397	(7.92) 0.312
-65	(10.49) 0.413	(8.33) 0.328
-73	(12.09) 0.476	(9.93) 0.391
-63	(14.10) 0.555	(11.94) 0.470
-66	(15.09) 0.594	(12.93) 0.509
-69	(15.60) 0.614	(13.44) 0.529
-74	(17.09) 0.673	(14.94) 0.588
-70	(17.60) 0.693	(15.44) 0.608
- 71	(21.08) 0.830	(18.92) 0.745
-72	(21.62) 0.851	(19.46) 0.766

samtec.com?STMM or samtec.com?ZSTMM

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

STMM-110-02-G-D STMM-125-02-G-D STMM-105-02-T-D-SM-K STMM-105-02-S-D STMM-105-02-G-D STMM-107-02-S-D STMM-105-02-L-D STMM-113-02-S-D STMM-110-01-T-D STMM-112-02-G-D STMM-107-02-G-D STMM-110-02-S-D STMM-105-01-T-D STMM-110-02-G-D-SM-K-TR STMM-107-02-S-D-SM STMM-105-02-G-D-RA STMM-125-02-S-D-SM STMM-110-02-L-D STMM-125-02-T-D STMM-113-02-L-D STMM-105-02-G-D-SM STMM-105-02-S-D-SM STMM-113-02-T-D STMM-120-02-T-D STMM-110-02-T-D STMM-108-02-L-D STMM-105-02-L-D-SM STMM-108-02-T-D STMM-115-02-L-D STMM-120-02-S-D STMM-120-02-G-D STMM-115-02-F-D STMM-115-02-T-D STMM-108-02-G-D-RA STMM-125-02-S-D STMM-125-02-S-D-RA STMM-108-02-S-D-SM STMM-115-02-G-D STMM-105-01-G-D STMM-107-02-S-D-RA STMM-110-02-F-D-SM STMM-125-02-L-D STMM-112-02-L-D STMM-105-02-F-D-SM-K-TR STMM-108-02-G-D STMM-108-02-F-D STMM-105-02-L-D-RA STMM-112-02-G-D-SM STMM-107-02-L-D-SM STMM-105-02-S-D-RA STMM-105-02-T-D STMM-110-02-L-D-SM STMM-105-02-F-D-SM STMM-120-02-L-D STMM-108-02-L-D-SM-LC STMM-107-02-L-D STMM-105-02-S-D-SM-K-TR STMM-105-02-G-D-SM-K-TR STMM-125-02-L-D-SM STMM-110-02-G-D-05 STMM-107-02-T-D-SM STMM-110-02-G-D-SM-LC-K-TR STMM-112-01-T-D STMM-117-02-T-D-SM STMM-117-02-T-D STMM-116-02-T-D-SM STMM-116-01-L-D-SM STMM-105-02-G-D-SM-K STMM-104-02-L-D-SM STMM-105-02-T-D-SM STMM-107-02-G-D-SM STMM-112-02-T-D-SM STMM-120-02-T-D-SM-LC-TR STMM-106-02-T-D-SM-K-TR STMM-110-02-T-D-SM-K STMM-105-02-L-D-SM-K STMM-108-02-L-D-SM STMM-122-02-G-D STMM-110-02-F-D STMM-104-02-G-D-SM STMM-110-01-G-D STMM-105-02-F-D-SM-K STMM-108-02-S-D STMM-107-02-T-D-SM-K STMM-108-01-T-D STMM-112-02-T-D STMM-108-02-F-D-SM-K-TR STMM-105-02-F-D-RA STMM-107-02-T-D STMM-104-01-L-D-SM STMM-122-02-T-D STMM-105-02-G-D-SM-10-K-TR STMM-107-02-G-D-RA STMM-108-02-T-D-SM-K-TR STMM-108-02-G-D-SM-K-TR STMM-108-02-L-D-SM-TR STMM-105-02-S-D-SM-K STMM-105-02-G-D-P STMM-117-02-G-D STMM-108-02-G-D-SM