




LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00						
			L	REVISED PER ECO-14-011808	09AUG2014	AP	SB

- CONNECTOR ACCEPTS SIZE 20 DF PIN CONTACTS, RETENTION TINES ARE AN INTEGRAL PART OF INSERT.
- CONNECTOR COMPLIES WITH 108-40005 WHERE APPLICABLE.
- MOLDED PART MATERIAL: GLASS-FILLED PBT OR GLASS-FILLED NYLON, UL94V-0 RATED. COLOR: BLACK
- SHELL MATERIAL: STEEL PER ASTM A109.
- ZINC PLATED PER ASTM B633; TYPE II; CLASS SC1; YELLOW CHROMATE.
- TIN OR TIN-LEAD PLATED OVER COPPER UNDERPLATE.
- TIN PLATED OVER COPPER UNDERPLATE.
- ZINC PLATED .000200-.000400 THICK, YELLOW TRIVALENT CHROMIUM CHROMATE COATING.

OBSOLETE	STANDARD	8	NO	205210-8
	STANDARD	7	NO	205210-7
	SMALL PACK	5	NO	205210-6
	STANDARD	7	YES	205210-3
OBSOLETE	STANDARD	6	NO	205210-2
OBSOLETE	STANDARD	5	NO	205210-1
PACKAGING TYPE		SHELL FINISH	GROUNDING INDENTS	PART NUMBER
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. WELDON 7-19-85	TE Connectivity	
DIMENSIONS: INCHES		CHK J. GERACE 7-29-85		
		APVD V. KUMAR 7-31-85		
		PRODUCT SPEC		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	PLUG CONNECTOR, SIZE 4, 37 POSITION, AMPLIMITE™ HDP	
0 PLC ± -		—		
1 PLC ± -		—	SIZE CAGE CODE DRAWING NO	
2 PLC ± 0.13 [.005]		—	A2 00779 C=205210	
3 PLC ± -		—	RESTRICTED TO	
4 PLC ± -		—	—	
ANGLES ± -		—	SCALE 4:1 SHEET 1 OF 1 REV L	
FINISH SHELLS: SEE TABLE		WEIGHT —	CUSTOMER DRAWING	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[205210-8](#)